

Material Safety Data Sheet

Doosan Infracore Portable Power 1293 Glenway Drive Statesville, NC 28625

Doosan Protec Engine Fluid

Product Description:

Chemical/Trade Name: Chemical family/Classification:

Transportation Emergency Response

CHEMTREC: (800) 424-9300 or

Doosan Portable Power: (800) 633-5206

SECTION 1 COMPOSITION / INFORMATION ON INGREDIENTS

Chemical names and synonyms: Severe treat min. oils and additives

Ingredients considered hazardous to health: This product is not formulated to contain ingredients which have exposure limits established by U.S. agencies. It is not hazardous to health as defined by the European Union Dangerous Substances/Preparations Directives. See Section 15 for a regulatory analysis of the ingredients.

SECTION 2 HAZARD IDENTIFICATION

U.S. OSHA Hazard Communication Standard: Product assessed in accordance with OSHA 29 CFR

1910.1200 and determined not to be hazardous. **Emergency Response Data:** Brown liquid

DOT ERG No.: N/A

SECTION 3 FIRST AID MEASURES

Eye Contact: Flush thoroughly with water. If irritation occurs, call a physician.

Skin Contact: Wash contact areas with soap and water.

Inhalation: Not excepted to be a problem.

Ingestion: Not expected to be a problem. However, if greater than ½ liter (pint) ingested, seek medical

attention.

SECTION 4 FIRE FIGHTING MEASURES

Special Fire Fighting Procedures: Water of foam may cause frothing. Use water to keep fire exposed containers cool. Water spray may be used to flush spills away from exposure. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

Special Protective Equipment: For fires in enclosed areas, fire fighters must use self-contained breathing

Flammable Limits: LEL: NA UEL: NA

NFPA Hazard ID: Health: 0 Flammability: 1 Reactivity: 0





SECTION 5 ACCIDENTAL RELEASE MEASURES

Notification Procedures: Report spills as required to appropriate authorities. U.S. Coast Guard regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks.

Report spill to Coast Guard Toll free number: (800) 424-8802 In case of accident or road spill notify CHEMTREC: (800) 424-9300

Procedures if Material is Released or Spilled: Absorb on fire retardant treated sawdust, diatomaceous earth, etc. Shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal

Environmental Precautions: Prevent spills from entering storm sewers or drains and contact with soil.

SECTION 6 HANDLING AND STORAGE

Handling: No special precautions are necessary beyond normal good hygiene practices.

Storage: Do not store in open or unlabelled containers. Store away from strong oxidizing agents or combustible material.

SECTION 7 EXPOSURE CONTROL / PERSONAL PROTECTION

Eye Protection: Normal industrial eye protection practices should be employed.

Skin Protection: No special equipment required. However, good personal hygiene practices should

always be followed.

Exposure Limits: This product does not contain any components which have recognized exposure limits.

However, an exposure limit of 5.00 mg/m3 is suggested for oil mist.

SECTION 8 PHYSICAL AND CHEMICAL PROPERTIES

Typical physical properties are given below. Consult Product Data Sheet for specific details

Appearance: Liquid
Color: Brown
Odor: Mild
Odor Threshold-ppm: NE
pH: NA

Boiling Point: > 316°C (600°F)

Melting Point: NA

Flash Point C(F): > 215°C (419°F) (ASTM D-92)

Flammability: NE **Auto Flammability:** NE **Explosive Properties:** NA **Oxidizing Properties:** NA Vapor Pressure-mmHg 20°C: < 0.1 Vapor Density: NE **Evaporation Rate:** NE Relative Density, 15/4°C: 0.866 Solubility in Water: Negligible **Partition Coefficient:** > 3.5 Viscosity at 40°C, cSt: 105.8 Viscosity at 100°C, cSt: 15.0

Pour Point C(F): < -27°C (-16°F)

Freezing Point C(F): NE



www.doosanportablepower.com

Rev. A, 09/2010 Page 2 of 4



Volatile Organic Compound: NE

NA = Not Applicable NE = Not Established D = Decomposes

For further technical information, contact your marketing representative

SECTION 9 STABILITY AND REACTIVITY

Stability (Thermal, Light, Etc.):StableConditions to Avoid:Extreme HeatIncompatibility (Materials to Avoid):Strong Oxidizers

Hazardous Decomposition Products: Carbon Monoxide, Metal Oxides, Elemental Oxides

Hazardous Polymerization: Will not occur

SECTION 10 DISPOSAL CONSIDERATIONS

Waste Disposal: Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is formulated to contain materials which are listed hazardous wastes.

SECTION 11 REGULATORY INFORMATION

Governmental Inventory Status: All components comply with TSCA, EINECS/ELINCS, AICS, MITI, and DSL.

EU Labeling: EU labeling not required

U.S. Superfound Amendments and Reauthorization act (SARA) Title III: This product contains no "EXTREMELY HAZARDOUS SUBSTANCES".

SARA: (311/312) REPORTABLE HAZARD CATEGORIES: None

This product contains no chemicals subject to the supplier notification requirements of SARA (313) toxic release program.

The following product ingredients are cited on the lists below:

| CHEMICAL NAME: | CAS NUMBER | LIST CITATIONS |
|---------------------------------------|------------|----------------|
| ZINC (Element Analysis) (0.13%) | 7440-66-6 | 22 |
| CHLORINE (Elemental Analysis) (0.02%) | 7782-50-5 | 22 |

REGULATORY LISTS SEARCHED

| 1 = ACGHI ALL | 8 = IARC 2B | 15 = TSCA 12b | 22 = MI 293 |
|---------------|---------------|-------------------|-------------|
| 2 = ACGIH A1 | 9 = OSHA CARC | 16 = CA P65 CARC | 23 = MN RTK |
| 3 = ACGIH A2 | 10 = OSHA Z | 17 = CA P65 REPRO | 24 = NJ RTK |
| 4 = NTP CARC | 11 = TSCA 4 | 18 = CA RTK | 25 =NJ RTK |
| 5 = NTP SUS | 12 = TSCA 5a2 | 19 = FL RTK | 26 = RI RTK |
| 6 = IARC 1 | 13 = TSCA e | 20 = IL RTK | |

7 = IARC 2A 14 = TSCA 6 21 = LA RTK

Code Key: CARC= Carcinogen SUS= Suspected Carcinogen REPRO= Reproductive



Rev. A, 09/2010 Page 3 of 4



The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.