

All tools conform to 98/37/EC and 2000/14/EC Annex VI Part 1
using standards EN292, EN28662-5

Tool Type	Model	Antivib?	Impact Frequency	Impact Energy @ 5 bars	RPM	Air Consumption	Piston Bore	Piston Stroke	Measured average noise level @ 6 bars	Guaranteed noise level @ 6 bars	Hand Arm Vibrations 1 axis	Hand Arm Vibrations 3 axis	Weight	Shank Size	Retainer	Length without chisel	CPN
			[bpm]	[J]	[rpm]	[m³/min]	[mm]	[mm]	[dB(A)]	[dB(A)]	[m/s²]	[m/s²]	[kg]	[mm]		[mm]	
Paving Breakers	IR15BS	No	1200	40J		0.75	36	168	101.7	103	11.1	9.1	16.0	22Hx82	Latch	609	85040152
													16.3	25Hx108	Latch	635	85040137
	IR15BV	Yes	1200	40J		0.75	36	168	101.7	103	2.8	4.1	15.3	22Hx82	Latch	644	85040160
													15.6	25Hx108	Latch	670	85040145
	IR20BS	No	1320	50J		1.30	40	136	104	105			21.7	25Hx108	Latch	659	80028491
													22.7	28Hx160	Latch	659	80028509
	IR20BV	Yes	1320	50J		1.30	40	136	104	105	2.5	5.1	20.8	25Hx108	Latch	659	80028517
													21.8	28Hx160	Latch	659	80028525
	IR25BS	No	1320	55J		1.30	42	136	106.9	108	15.9	11.5	25.9	28Hx160	Latch	659	80028681
													25.9	32Hx160	Latch	659	80028699
	IR25BV	Yes	1320	55J		1.30	42	136	106.9	108	4.1	5.2	24.3	25Hx108	Latch	659	80028707
													25.0	28Hx160	Latch	694	80028715
													25.0	32Hx160	Latch	694	80028723
	IR30BS	No	1200	70J		1.70	45	162	108.4	110	10.7	11.9	30.9	28Hx160	Latch	700	85040061
													30.9	32Hx160	Latch	659	85040046
	IR30BV	Yes	1200	70J		1.70	45	162	108.4	110	4.3	5.3	30.0	28Hx160	Latch	735	85040079
													30.0	32Hx160	Latch	735	85040053
	IR40BS	No	960	105J		1.85	45	182	108.2	110	13.3	8.8	40.9	28Hx160	Latch	765	85040020
													40.9	32Hx160	Latch	765	85040004
	IR40BV	Yes	960	105J		1.85	45	182	108.2	110	7.9	3.5	40.0	28Hx160	Latch	800	85040038
													40.0	32Hx160	Latch	800	85040012

Doosan purchased Bobcat Company from Ingersoll-Rand Company in 2007. Any reference to Ingersoll-Rand Company or use of trademarks, service marks, logos, or other proprietary identifying marks belonging to Ingersoll-Rand Company in this manual is historical or nominative in nature, and is not meant to suggest a current affiliation between Ingersoll-Rand Company and Doosan Company or the products of either.

'V' tools feature vibration dampening
Check the *Pneumatic Tools CD* for more information

All tools conform to 98/37/EC and 2000/14/EC Annex VI Part 1
using standards EN292, EN28662-5

Tool Type	Model	Antivib?	Impact Frequency	Impact Energy @ 5 bars	RPM	Air Consumption	Piston Bore	Piston Stroke	Measured average noise level @ 6 bars	Guaranteed noise level @ 6 bars	Hand Arm Vibrations 1 axis	Hand Arm Vibrations 3 axis	Weight	Shank Size	Retainer	Length without chisel	CPN
			[bpm]	[J]	[rpm]	[m³/min]	[mm]	[mm]	[dB(A)]	[dB(A)]	[m/s²]	[m/s²]	[kg]	[mm]		[mm]	
Chipping Hammers	IR2PS	No	2850			0.35		50	106	107		6.9	2.6	15CHx55	Spring	300	93482990
	IR3PS	No	3850			0.35		37	107	107		2.9	3.5	19Hx50	Spring	335	01338060
	IR5PS	No	2650			0.43		60	107	107		6.7	5.0	19Hx50	Spring	408	01337674
Pick Hammers	IR9PS	No	1620	26J		0.90	34	115	104.1	105	13.3		10.5	22Hx82	Latch	470	85041929
													9.5	22Hx82	Screw	470	85041952
													9.5	23Rx70	Screw	470	85041945
													9.5	25Rx75	Screw	470	85041937
	IR10PV	Yes	2040	26J		1.00	36	118	99.2	101	5.1	6.1	11.5	22Hx82	Latch	525	85042000
													10.5	22Hx82	Screw	516	85041994
													10.5	25Rx75	Screw	516	85041986
	IR12PS	No	1200	40J		0.90	36	163	103.4	105	9.1		13.5	22Hx82	Latch	617	85041960
													12.5	22Hx82	Screw	612	85042042
													12.5	25Rx75	Screw	612	85041978
	IR12PV	Yes	1260	40J		0.90	36	165	100.6	102	3.8	5.6	13.5	22Hx82	Latch	644	85042034
													12.5	22Hx82	Screw	635	85042026
													12.5	25Rx75	Screw	635	85042018
Jack Hammers	IR5JS	No	3450			0.48					9.3		5.0	19Hx50	Spring		01338524
	IR17JS	No	2040		170	2.80	55	50	116		15.8		17.8	22Hx108	Spring	643	85043370
	IR17JV	Yes	2040		170	2.80	55	50	116		6.1		17.8	22Hx108	Spring	643	85043388
	IR23JS	No	2100		130	4.80	70	50	117		19.0		23.5	22Hx108	Spring	720	85043396
	IR23JV	Yes	2100		130	4.80	70	50	117		6.7		23.5	22Hx108	Spring	720	85043404