

Portable Power Service News | Accessories

Accessories for pneumatic tools DCT17JS-JV and DCT23JS-JV

Due to a production stop of items listed below Doosan regrets to inform you that some shanks and bits for the Jackhammers will be replaced by a newer type.

This change requires customers using the previous tapered shanks and bits to purchase the new shank and bit combination.

This threaded rod and connection design allows for higher productivity and removes the risk of bits detaching from the shank rod during drilling operations.

Original configuration:

Jack rod extension 19 mm taper	22H x 108	460	19 mm	85041697
	22H x 108	610	19 mm	85041705
	22H x 108	915	19 mm	85041713
	22H x 108	1220	19 mm	85041721
	22H x 108	1830	19 mm	85041739
	22H x 108	2435	19 mm	85041747
All steel cross bit (Fitting on extensions)	19 mm		35	85041754
	19 mm		38	85041762
	19 mm		41	85041770
	19 mm		44	85041788
	19 mm		48	85041796
	19 mm		51	85041804
Tungsten carbide cross bit (Fitting on extensions)	19 mm		35	85041812
	19 mm		38	85041820
	19 mm		41	85041838
	19 mm		44	85041846
	19 mm		48	85041853
	19 mm		51	85041861

TO BE REPLACED



Jack Rod Extension Taper

+

Steel or tungsten cross bit



+



New configuration:

Fixed Length Shank Rod

Hex Shank Rod-Rope thread + Tungsten Carbide Button Bit



Hex shank rod cpn

46550981
46550982
46550983
46550984
46550985
46550986

Description

22x108 Hex Shank Rod 460mm below collar R25 rope thread
22x108 Hex Shank Rod 610mm below collar R25 rope thread
22x108 Hex Shank Rod 915mm below collar R25 rope thread
22x108 Hex Shank Rod 1220mm below collar R25 rope thread
22x108 Hex Shank Rod 1830mm below collar R25 rope thread
22x108 Hex Shank Rod 2435mm below collar R25 rope thread

Variable Length with Extensions Shank Rod

Hex Shank Rod-Rope thread + R25 coupling+ Extension Rod + Tungsten Carbide Button Bit



Extension parts cpn

46550993
46550994

Description

800mm extension rod R25 thread on both ends
R25 coupling for use with shanks and extension rods

Drill Bits



Tungsten Carbide Button Bit cpn

46550987
46550988
46550989
46550990
46550991
46550992

Description

5mm R 25 rope thread Tungsten Carbide Button Bit
38mm R 25 rope thread Tungsten Carbide Button Bit
41mm R 25 rope thread Tungsten Carbide Button Bit
44mm R 25 rope thread Tungsten Carbide Button Bit
48mm R 25 rope thread Tungsten Carbide Button Bit
51mm R 25 rope thread Tungsten Carbide Button Bit

NOTE:



The above arrangement using the extension coupling can only be used with button bits 44mm and above due to the external diameter of the coupling being 38mm.

Using a smaller than 44mm bit would block the free removal of debris from the drill hole.

www.doosanportablepower.com



Doosan Infracore
Portable Power